



Anemometers



Model TA440

Thermal Anemometers

Model TA410

The Model TA410 is a solid choice for a digital Air Velocity Meter, without compromising accuracy or precision. Excellent for troubleshooting HVAC systems and conducting commissioning work.

Models TA430 and TA440

The Models TA430 and TA440 are like having multiple meters for the price of one, yet they are simple to operate. Purchase instruments with a straight or articulated probe—all in one compact package.

Features and Benefits

- Accurate air velocity measurement
- Large, easy to read display
- Calibration certificate included

Models TA430 and TA440

- Simultaneously measures temperature and velocity
- Displays up to three measurements simultaneously
- Calculates volumetric flow, and actual/standard velocity
- Articulated probe versions available
- Data logging and LogDat2™ downloading software included
- Measures humidity (TA440)

Applications

- HVAC system performance
- Commissioning
- Plant maintenance
- Critical environment certification
- Duct traverses

Accurate. Reliable. Every Time.



Anemometers

Thermal Anemometers

Models TA440 and TA430

Specifications

Models TA410, TA430 and TA440

Velocity

Range (TA410) 0 to 20 m/s (0 to 4,000 ft/min)

Range (TA430, TA440)

0 to 30 m/s (0 to 6,000 ft/min)

Accuracy (TA410)^{1&2} ±5% of reading or ±0.025 m/s (±5 ft/min), whichever is greater

Accuracy (TA430, TA440)^{1&2}

±3% of reading or ±0.015 m/s (±3 ft/min), whichever is greater

Resolution 0.01 m/s (1 ft/min)

Duct Size (TA430, TA440)

Dimensions 1 to 635 cm in increments of 0.1 cm

(1 to 250 inches in increments of 0.1 in.)

Volumetric Flow Rate (TA430, TA440)

Range Actual range is a function of velocity, and duct size

Temperature

Range (TA410, TA430)

-18 to 93°C (0 to 200°F)

Range (TA440)

-10 to 60°C (14 to 140°F)

Accuracy³ ±0.3°C (±0.5°F)

Resolution 0.1°C (0.1°F)

Relative Humidity (TA440 only)

Range 0 to 95% RH

Accuracy⁴ ±3% RH

Resolution 0.1% RH

Wet Bulb Temperature (TA440 only)

Range 5 to 60°C (40 to 140°F)

Resolution 0.1°C (0.1°F)

Dew Point (TA440 only)

Range -15 to 49°C (5 to 120°F)

Resolution 0.1°C (0.1°F)

Instrument Temperature Range

Operating (Electronics)

5 to 45°C (40 to 113°F)

Model TA410, TA430 Operating (Probe)

-18 to 93°C (0 to 200°F)

Model TA440 Operating (Probe)

-10 to 60°C (14 to 140°F)

Storage -20 to 60°C (-4 to 140°F)

Data Storage Capabilities (TA430, TA440)

Range 12,700+ samples and 100 test IDs

Logging Interval (TA430, TA440)

1 second to 1 hour

Time Constant (TA430, TA440)

User selectable

External Meter Dimensions

8.4 cm x 17.8 cm x 4.4 cm (3.3 in. x 7.0 in. x 1.8 in.)

Meter Weight with Batteries

0.27 kg (0.6 lbs.)

Meter Probe Dimensions

Probe Length 101.6 cm (40 in.)

Probe Diameter of Tip 7.0 mm (0.28 in.)

Probe Diameter of Base 13.0 mm (0.51 in.)

Articulating Probe Dimensions

Articulating Section Length 19.7 cm (7.8 in.)

Diameter of Articulating Knuckle 9.5 mm (0.38 in.)

Power Requirements

Four AA-size batteries or AC adapter

	TA410	TA430, TA430-A	TA440, TA440-A
Velocity range 0 to 4000 ft/min (0 to 20.00 m/s)	•		
Velocity range 0 to 6000 ft/min (0 to 30.00 m/s)		•	•
Temperature	•	•	•
Flow		•	•
Humidity, wet bulb, dew point			•
Probe	Straight	Straight or -A articulated	Straight or -A articulated
Variable time constant		•	•
Manual data logging		•	•
Auto save data logging			•
Statistics		•	•
Review data		•	•
LogDat2 downloading software		•	•
Free Certificate of Calibration	•	•	•

¹ Temperature compensated over an air temperature range of 5 to 65°C (40 to 150°F).

² The accuracy statement begins at 30 ft/min through 4000 ft/min (0.15 m/s through 20 m/s) for the Model TA410, and 30 ft/min through 6,000 ft/min (0.15 m/s through 30 m/s) for Models TA430 and TA440.

³ Accuracy with instrument case at 25°C (77°F), add uncertainty of 0.03°C/°C (0.05°F/°F) for change in instrument temperature.

⁴ Accuracy with probe at 25°C (77°F). Add uncertainty of 0.2% RH/°C (0.1% RH/°F) for change in probe temperature. Includes 1% hysteresis.

Specifications subject to change without notice.

AIRFLOW Instruments, TSI Instruments Ltd.

Stirling Road, Cressex Business Park, High Wycombe, Bucks, HP12 3ST, United Kingdom

UK Tel: +44 149 4 459200 E-mail: info@airflowinstruments.co.uk

France Tel: +33 491 11 87 64 E-mail: tsifrance@tsi.com

Germany Tel: +49 241 523030 E-mail: tsigmbh@tsi.com

Contact your local AIRFLOW Distributor or visit our website www.airflowinstruments.co.uk for more detailed specifications.

